

Technical Product Data sheet 03.12

Product Name	Plas-seal
Product reference	PP74
Product description	<p>Clear water borne binding sealer for application to interior and exterior paving, concrete and stone. Application of Plas-seal enhances the colour of treated surfaces and increases resistance to wear and mild chemical attack. Additional coats will gradually increase sheen.</p> <p>If required, a slip resistant additive is available which can be added to the final coat of Plas-seal.</p>
Uses	Penetrating binder/sealer for exterior paving, concrete and stone
Pack sizes availability	5 & 20 litres
Colour range	Clear
Specific gravity	Approx 1.0
Flash point	Non flammable
Recommended Spreading rate	Approx. 3 - 7 m ² /litre depending on surface absorbency
Solids content	Approx 15% w/w
Drying time	Approx 1 hour 20°C 65%RH depending on level of penetration
Over-coating time	Approx 4 - 6 hours 20°C 65%RH
Minimum application temperature	<p>Air and surface temperature should be 5°C and rising.</p> <p>Do not apply during damp or frosty weather or when rain is imminent</p>

Recommended dry film thickness	N/A
Method of application	Brush, roller or low pressure spray.
Preparation	<p>Surfaces must be clean, sound and dry and prepared in accordance with BS6150 Painting of buildings – code of practice.</p> <p>Treat organic growth with fungicidal solution.</p> <p>Remove weeds etc or treat with a proprietary herbicide</p>
Storage life	Min 12 months in original sealed containers. Protect from frost and direct heat
Thinning/cleaning	<p>Do not thin</p> <p>Wash equipment immediately after use with clean water and detergent.</p>
Safety precautions	Refer to the safety data sheet before use
Volatile organic content (voc)	<p>Limit for this product Cat A/h 30g/l (2010).</p> <p>This product contains maximum 25g/l VOC</p>
Disposal	<p>As supplied or containing liquid product – non hazardous waste code</p> <p>08 01 12 waste paint and varnish other than those mentioned in 08 01 11</p> <p>Used containers drained/rigorously scraped out and containing only dry residues: categorised as non-hazardous with waste code 15 01 02 (plastic package)</p> <p>If mixed with other wastes the above waste codes may not be applicable</p>