

## Technical Product Data sheet 07.12

Product Name	Spray Textured Masonry Paint
Product reference	PP01
Product description	<p>A highly durable long life spray applied textured coating for the protection and decoration of most external masonry surfaces. Spay Textured masonry paint is a solvent borne high build product based on plasticised alkyd technology with reinforcing fibres.</p> <p>Contains a fungicide to inhibit mould growth on the surface</p> <p>Available in coarse texture (Grade 25) medium texture (Grade 15) and fine texture finishes</p>
Uses	Long life exterior masonry decoration and protection
Pack sizes availability	20 litres
Colour range	White plus 12 standard colours. Special colours on request subject to minimum quantities.
Specific gravity	Approx 1.2
Flash point	Flammable Flash point approx 40deg C
Recommended Spreading rate	Approx 1.25 litres/m <sup>2</sup> (16 m <sup>2</sup> per 20 litre container)
Solids content	<p>Approx 75% w/w</p> <p>Approx 60% v/v</p>
Drying time	Approx 24 hours 20°C 65%RH (2 – 3 weeks for full cure)
Over-coating time	Approx 24 hours 20°C 65%RH
Minimum application temperature	Do not apply during frosty or foggy weather or

	onto damp surfaces
Recommended dry film thickness	Approximately 750 microns
Method of application	Air assisted airless (Graco President 10:1 HMSU) or hopper spray
Preparation	<p>Surfaces must be clean, sound and dry and prepared in accordance with BS6150 Painting of buildings – code of practice.</p> <p>Treat organic growth with fungicidal solution.</p> <p>Remove any unsound previous coatings and weak material and repair with suitable exterior repair products before coating with Tinted Stabiliser.</p>
Storage life	<p>Min 12 months in original sealed containers.</p> <p>Protect from frost and direct heat</p>
Thinning/cleaning	<p>Thin where necessary with D40 Solvent or white spirit. Do not exceed 1 part solvent to 20 parts of coating.</p> <p>Wash equipment immediately after use with D40 solvent or white spirit.</p>
Safety precautions	Refer to the safety data sheet before use
Volatile organic content (voc)	<p>Limit for this product Cat A/c 430g/l (2010).</p> <p>This product contains maximum 300g/l VOC</p>
Disposal	<p>When this coating, in its liquid state, as supplied or skinned, becomes a waste, it is categorised as hazardous waste, with code 08 01 11 (list of hazardous wastes)</p> <p>Used containers, drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 04 (list of wastes)</p> <p>If mixed with other wastes the above waste codes may not be applicable</p>

