

Technical Product Data sheet 01.12

Product Name	S/B Stabiliser
Product reference	PP22
Product description	S/B Stabiliser is a solvent borne clear masonry binding primer based on acrylic resins. Improves adhesion of finishing coatings to friable, chalking masonry surfaces.
Uses	Primer/stabiliser for friable or chalky masonry surfaces
Pack sizes availability	5 & 25 litres
Colour range	Clear.
Specific gravity	Approx 0.8
Flash point	Flammable Flash point approx 40deg C
Recommended Spreading rate	Approx. 5 – 8 m <sup>2</sup> /litre depending on surface porosity Ensure all applied material is absorbed into the surface
Solids content	Approx 13% w/w
Drying time	Approx 2 - 4 hours 20°C 65%RH depending on depth of penetration.
Over-coating time	Approx 12 hours 20°C 65%RH
Minimum application temperature	The performance of S/B Stabiliser is not adversely affected by low temperatures. However, do not apply during frosty or foggy weather or onto wet surfaces
Recommended dry film thickness	N/A
Method of application	Ideally apply by brush working well into the surface.

	May be low pressure sprayed if required
Preparation	<p>Surfaces must be clean, sound and dry and prepared in accordance with BS6150 Painting of buildings – code of practice.</p> <p>Treat organic growth with fungicidal solution.</p> <p>Remove any unsound previous coating and weak material and repair with suitable exterior repair products before coating with S/B Stabiliser.</p>
Storage life	<p>Min 12 months in original sealed containers.</p> <p>Protect from frost and direct heat</p>
Thinning/cleaning	<p>Do not thin.</p> <p>Wash equipment immediately after use with D40 solvent or white spirit.</p>
Safety precautions	Refer to the safety data sheet before use
Volatile organic content (voc)	<p>Limit for this product Cat A/h 750g/l (2010).</p> <p>This product contains maximum 700g/l VOC</p>
Disposal	<p>When this coating, in its liquid state, as supplied or skinned, becomes a waste, it is categorised as hazardous waste, with code 08 01 11 (list of hazardous wastes)</p> <p>Used containers, drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 04 (list of wastes)</p> <p>If mixed with other wastes the above waste codes may not be applicable</p>