

Technical Product Data sheet 09.11

Product Name	Highbuild Texture W/B
Product reference	PP45
Product description	Water borne high build textured masonry coating formulated for trowel and roll application. Based on modified vinyl acrylic resin, Highbuild W/B exhibits excellent adhesion to most masonry surfaces and may be textured using appropriate rollers to provide attractive finishes.
Uses	Decoration and protection of a wide range of masonry surfaces and primed exterior plywood.
Pack sizes availability	10 & 20 litres
Colour range	White plus standard colour card. Special colours on request subject to minimum batch sizes
Specific gravity	Approx 1.7
Flash point	Non flammable
Recommended Spreading rate	Approx. 1 litre/m ²
Solids content	Approx 77% w/w Approx 60% v/v
Drying time	Approx 4 hours 20°C 65%RH
Over-coating time	Approx 16 hours 20°C 65%RH
Minimum application temperature	Air and surface temperature should be 5°C and rising. Do not apply during damp or frosty weather or when rain is imminent

Recommended dry film thickness	Approximately 600 microns
Method of application	Brush, roller or airless spray
Preparation	<p>Surfaces must be clean, sound and dry and prepared in accordance with BS6150 Painting of buildings – code of practice.</p> <p>Bare metal surfaces must be adequately primed.</p>
Storage life	<p>Min 12 months in original sealed containers.</p> <p>Protect from frost and direct heat</p>
Thinning/cleaning	<p>Thin where necessary with clean water. Do not exceed 1 part water to 10 parts of Highbuild W/B.</p> <p>Wash equipment immediately after use with water and detergent</p>
Safety precautions	Refer to the safety data sheet before use
Volatile organic content (voc)	<p>Limit for this product Cat A/c 40g/l (2010).</p> <p>This product contains maximum 5g/l VOC</p>
Disposal	<p>As supplied or containing liquid product – non hazardous waste code</p> <p>08 01 12 waste paint and varnish other than those mentioned in 08 01 11</p> <p>Used containers drained/rigorously scraped out and containing only dry residues:</p> <p>categorised as non-hazardous with waste code</p> <p>15 01 02 (plastic package)</p> <p>and 15 01 04 (metal package)</p>